

SlimAge 121TSA - 12,1" TFT / Analog

LCD Display	12.1" TFT Active Matrix Panel
Display Size	246 x 184.5 mm
Pixel Pitch	0.3075 x 0.3075 mm
Display Mode	VGA 640x350 (70Hz) VGA 720x400 (70Hz) VGA 640x480 (60/72/75Hz) SVGA 800x600 (60/72/75Hz) Mac. 832x624 (75Hz)
Max. Resolution	800 x 600
Contrast Ratio	150
Brightness	250 cd/m²
Response Time	30mS(Rising), 20mS (Falling)
Display Colors	16M(dithering)
Viewing Angle	+40° ~ -40°(L/R), +10° ~ -20°(U/D) min.
Input Signal	
Video	R.G.B Analog 0.7V Peak-to-Peak
Sync	TTL Positive or Negative
Signal Connector	15Pin Mini D-sub
Front Control	Power Switch, Menu, Select (Up, Down), Auto-Adjustment
OSD	Auto-Adjustment, Contrast, Helligkeit, Clock, Phase, H-Position , V-position, Farb-Temperatur, Load default
Plug & Play	DDC1/2B
Optional	Touch Screen Video in: PAL/NTSC & S-video/AV connector Audio System: 1W per Channel
Power	Universal 90-240V, 12V/35W
Dimensions	3312 x 236 x 73 mm
Weight (Net)	2,2Kg
Certification	FCC-B, CE, UL, TUV

